
## Durelloy-TGP HEAT TREATED ALLOY





Durelloy-TGP is produced from Durelloy hot roll heat treat 28-32 Rc bars, then precision turned, ground, and flawlessly polished to exacting sizes. Durelloy-TGP eliminates costly machining to size at your plant, which helps reduce downtime. Durelloy-TGP allows you to produce long, straight keyways without bowing problems.

## **Features And Advantages**

- · Precision tuned, ground and polished
- Not cold drawn, free from drawing stresses
- Straightness guaranteed prior to shipment
- Good weldability
- Free machining
- Ultra fine grain microstructure
- Wear resistant
- Eliminates premature fatigue/failure due to hardness and high luster
- Stress relieved

## **Applications**

- Arbors
- Gear shafts
- Journals
- Line shafts
- Lead screws
- Drive shafts
- Motor shafts
- Crank shafts
- Armature shafts
- Cement mill shafts

- Textile equipment
- Mining equipment
- Generator shafts
- Pinions
- Piston rods
- Push rods
- Spindles
- Feed screws
- Tie rods

## **Standard Tolerances**

- Standard finish of 8 micro-inches
- 1/4" to 4" diameter: +.000" to -.002" tolerance
- Over 4" diameter: +.000" to -.003" tolerance
- Closer tolerance of +/- .0005" available

All shipments of Durelloy-TGP are specially oiled, then wrapped or tubed and delivered in perfect condition. All bars are inspected prior to shipping for straightness and tolerances.

Durelloy-TGP Rounds 1/8" Diameter Rounds in 1/16" Increments							
1/8 3/16	3/4 13/16	1-5/16 1-3/8	1-7/8 1-15/16	2-7/16 2-1/2	3 3-1/8	4 4-1/4	5-15/16 6
1/4 5/16 3/8	7/8 15/16 1	1-7/16 1-1/2 1-9/16	2 2-1/16 2-1/8	2-9/16 2-5/8 2-11/16	3-3/16 3-1/4 3-3/8	4-7/16 4-1/2 4-3/4	6-1/2 7 8
1/2 9/16	1-1/16 1-1/8	1-5/8 1-11/16	2-3/16 2-1/4	2-3/4 2-13/16	3-7/16 3-1/2	4-15/16 5	
5/8 11/16	1-3/16 1-1/4	1-3/4 1-13/16	2-5/16 2-3/8	2-7/8 2-15/16	3-3/4 3-15/16	5-7/16 5-1/2	

Lengths: 20' R/L. Larger sizes and metric sizes in stock.